

200QJ10						高度重量仅供参考			
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter	配用电线截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJH10-47	10	47	4	184	2″	2.5	1337	79
2	200QJH10-62		62	5.5			2.5	1472	90
3	200QJH10-78		78	7.5			4	1582	101
4	200QJH10-93		93	7.5			4	1722	110
5	200QJH10-109		109	9.2			6	1851	129
6	200QJH10-124		124	9.2			6	1977	134
7	200QJH10-140		140	11			6	2122	146
8	200QJH10-155		155	13			6	2256	157
9	200QJH10-171		171	13			6	2417	171
10	200QJH10-186		186	15			6	2527	181
11	200QJH10-202		202	15			6	2761	201
12	200QJH10-217		217	18.5			10	2871	209
13	200QJH10-233		233	18.5			10	2981	238
14	200QJH10-248		248	18.5			10	3157	246
15	200QJH10-264		264	22			16	3267	254
16	200QJH10-279		279	22			25	3482	274
17	200QJH10-295		295	22			25	3592	282
18	200QJH10-310		310	25			25	3702	306
19	200QJH10-326		326	25			25	3812	314
20	200QJH10-341		341	25			35	3922	322
21	200QJH10-355		355	30			35	4032	355

200QJ20						高度重量仅供参考			
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter	配用电线截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJH20-13	20	13	3	184	2″	2.5	820	79
2	200QJH20-26		26	3				940	90
3	200QJH20-39		39	4				1377	101
4	200QJH20-52		52	5.5				1472	110
5	200QJH20-65		65	5.5				1582	129
6	200QJH20-78		78	7.5			4	1722	134
7	200QJH20-91		91	9.2			4	1851	146
8	200QJH20-104		104	11			4	1977	157
9	200QJH20-117		117	13			6	2122	171
10	200QJH20-130		130	15			6	2256	181
11	200QJH20-143		143	18.5			6	2417	201
12	200QJH20-156		156	18.5			10	2527	209
13	200QJH20-169		169	22		2.5″	10	2761	238
14	200QJH20-182		182	22			10	2871	246
15	200QJH20-195		195	22			10	2981	254
16	200QJH20-208		208	25			10	3157	274
17	200QJH20-221		221	25			10	3267	282

18	200QJH20-234		234	30			10	3482	304
19	200QJH20-247		247	30			16	3592	314
20	200QJH20-260		260	30			16	3702	322
21	200QJH20-273		273	30			16	3812	330
22	200QJH20-286		286	37			16	4013	355
23	200QJH20-299		299	37			16	4141	363
24	200QJH20-312		312	37			16	4251	371
25	200QJH20-325		325	37			16	4361	379
26	200QJH20-338		338	40			25	4581	406
27	200QJH20-351		351	40			25	4691	414
28	200QJH20-374		374	40			25	4801	422
29	200QJH20-378		378	45			25	4911	430
30	200QJH20-390		390	45			25	5021	435

200QJ32 高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m ³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter	配用电线截面积 cable section mm ²	机组高度 Height mm	机组重量 Weight kg
1	200QJH32-13	32	13	4	184	3"	6	1197	95
2	200QJH32-26		26	5.5			6	1346	107
3	200QJH32-39		39	7.5			6	1454	116
4	200QJH32-52		52	9.2			6	1598	130
5	200QJH32-65		65	11			6	1901	145
6	200QJH32-78		78	13			6	1952	158
7	200QJH32-91		91	15			10	2045	173
8	200QJH32-104		104	18.5			10	2162	204
9	200QJH32-117		117	18.5			10	2281	211
10	200QJH32-130		130	22			10	2420	224
11	200QJH32-143		143	22			10	2539	231
12	200QJH32-156		156	25			16	2693	248
13	200QJH32-169		169	30			16	2847	268
14	200QJH32-182		182	30			16	2966	275
15	200QJH32-195		195	37			25	3150	289
16	200QJH32-208		208	37			25	3269	296
17	200QJH32-221		221	37			25	3388	303
18	200QJH32-234		234	45			35	3562	330
19	200QJH32-247		247	45			35	3861	337
20	200QJH32-260		260	45			35	3800	344
21	200QJH32-273		273	45			35	3919	351
22	200QJH32-286		286	55			35	4118	378
23	200QJH32-299		299	55			35	4237	385
24	200QJH32-312		312	55			50	4356	392
25	200QJH32-330		330	63		4"	50	3955	295
26	200QJH32-350		350	63			50	4080	310
27	200QJH32-370		370	75			70	4205	325
28	200QJH32-390		390	75			70	4430	340
29	200QJH32-410		410	75			70	4555	355
30	200QJH32-430		430	75			70	4680	370
31	200QJH32-450		450	75			70	4805	385
32	200QJH32-470		470	90			95	5080	400
33	200QJH32-490		490	90			95	5205	415

编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter	配用电线截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJH50-13	50	13	4	184	3"	6	1228	98
2	200QJH50-26		26	7.5			6	1427	115
3	200QJH50-39		39	9.2			6	1572	132
4	200QJH50-52		52	13			6	1787	156
5	200QJH50-65		65	15			10	1962	174
6	200QJH50-78		78	18.5			10	2167	208
7	200QJH50-91		91	22			10	2362	224
8	200QJH50-104		104	25			16	2557	244
9	200QJH50-117		117	30			16	2807	267
10	200QJH50-130		130	30			16	2957	277
11	200QJH50-143		143	37			25	3207	294
12	200QJH50-156		156	37			25	3357	304
13	200QJH50-169		169	37			25	3507	314
14	200QJH50-182		182	45			25	3726	344
15	200QJH50-195		195	45			25	3912	354
16	200QJH50-208		208	45			35	4062	364
17	200QJH50-221		221	55			35	4050	394
18	200QJH50-234		234	55			35	4200	404
19	200QJH50-247		247	55			35	4350	414
20	200QJH50-260		260	55			35	4500	424
21	200QJH50-273		273	63		4"	50	4762	478
22	200QJH50-286		286	63			50	4912	488
23	200QJH50-299		299	75			70	5202	518
24	200QJH50-312		312	75			70	5352	528
25	200QJH50-332		332	75			70	5502	538
26	200QJH50-352		352	90			70	5652	548
27	200QJH50-372		372	90			70	5894	578
28	200QJH50-392		392	90			70	6044	588
29	200QJH50-412		412	90			70	6194	598
30	200QJH50-432		432	100			95	6494	608
31	200QJH50-452		452	100			95	6644	618
32	200QJH50-472		472	100			95	6887	628
33	200QJH50-492		492	110			120	7037	735
34	200QJH50-512		512	110			120	7178	755

200QJ63高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter inch	配用电线截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJH63-15		15	5.5			2.5	885	98
2	200QJH63-30		30	9.2			4	1340	115
3	200QJH63-45		45	13			6	1530	132
4	200QJH63-60		60	18.5			10	1735	156
5	200QJH63-75		75	25			10	1905	174

6	200QJH63-90	63	90	30	184	4"	10	2117	208
7	200QJH63-105		105	37			16	2400	227
8	200QJH63-120		120	37			16	2525	244
9	200QJH63-135		135	45			25	2775	267
10	200QJH63-150		150	50			25	2880	277
11	200QJH63-165		165	50			25	3005	294
12	200QJH63-180		180	55			25	3197	304
13	200QJH63-195		195	63			35	3425	327
14	200QJH63-210		210	63			35	3577	344
15	200QJH63-225		225	75			50	3700	347
16	200QJH63-240		240	75			50	3895	364
17	200QJH63-255		255	75			50	4020	381
18	200QJH63-270		270	90			70	4195	397
19	200QJH63-285		285	90			70	4320	414
20	200QJH63-300		300	90			70	4495	431

200QJ80 高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m ³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outlet diameter inch	配用电线截 面积 cable section mm ²	机组高度 Height mm	机组重量 Weight kg
1	200QJH80-17	80	17	7.5	184	4"	4	1182	93
2	200QJH80-34		34	11			6	1382	98
3	200QJH80-51		51	18.5			10	1627	103
4	200QJH80-68		68	22			10	1886	113
5	200QJH80-85		85	30			16	2192	120
6	200QJH80-102		102	37			16	2436	128
7	200QJH80-119		119	40			25	2681	138
8	200QJH80-136		136	45			25	2816	145
9	200QJH80-153		153	55			25	2910	158
10	200QJH80-170		170	55			25	3045	166
11	200QJH80-187		187	63			35	3245	174
12	200QJH80-204		204	75			35	3575	197
13	200QJH80-221		221	75			35	3710	205
14	200QJH80-238		238	90			50	3955	207
15	200QJH80-255		255	90			50	4090	215
16	200QJH80-272		272	90			50	4225	223
17	200QJH80-289		289	100			50	4485	235
18	200QJH80-306		306	100			50	4620	243
19	200QJH80-323		323	110			75	4755	251
20	200QJH80-340		340	110			75	4890	259