

175QJ10								
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outler diamete r inch	配用电线 截面积 cable section mm²	控制
1	175QJH10-15	10	15	3	163	2”	2.5	可根据用户需求匹配或厂家提出对应建议
2	175QJ1H0-30		30	3			2.5	
3	175QJH10-45		45	4			2.5	
4	175QJH10-60		60	4			2.5	
5	175QJH10-75		75	5.5			2.5	
6	175QJH10-90		90	5.5			2.5	
7	175QJH10-105		105	7.5			4	
8	175QJH10-120		120	7.5			4	
9	175QJH10-135		135	9.2			4	
10	175QJH10-150		150	9.2			4	
11	175QJH10-165		165	11			6	
12	175QJH10-180		180	13			10	
13	175QJH10-195		195	13			10	
14	175QJH10-210		210	15			10	
15	175QJH10-225		225	15			10	
16	175QJH10-240		240	18.5			16	
17	175QJH10-255		255	18.5			16	
18	175QJH10-270		270	18.5			25	
19	175QJH10-285		285	22			25	
20	175QJH10-300		300	22			25	
175QJ15								
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outler diamete r inch	配用电线 截面积 cable section mm²	控制
1	175QJH15-14	15	14	3	163	2”	2.5	可根据用户需求匹配或厂家提出对
2	175QJH15-28		28	3			2.5	
3	175QJH15-42		42	4			2.5	
4	175QJH15-56		56	5.5			2.5	
5	175QJH15-70		70	7.5			4	
6	175QJH15-84		84	7.5			4	
7	175QJH15-98		98	9.2			4	
8	175QJH15-112		112	9.2			4	
9	175QJH15-126		126	11			4	
10	175QJH15-140		140	11			6	
11	175QJH15-154		154	13			6	
12	175QJH15-168		168	15			10	
13	175QJH15-182		182	15			10	
14	175QJH15-196		196	18.5			10	
15	175QJH15-210		210	18.5			16	
16	175QJH15-224		224	22			16	

17	175QJH15-238		238	22			16	应 建 议
18	175QJH15-252		252	22			25	
19	175QJH15-266		266	25			25	
20	175QJH15-278		278	25			25	

175QJ20

编号 NO.	型号 Type	流量 Flow rate m ³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outler diamete r inch	配用电线 截面积 cable section mm ²	控制
1	175QJH20-26	20	26	3	163	2"	2.5	可 根 据 用 户 需 求 匹 配 或 厂 家 提 出 对 应 建 议
2	175QJH20-39		39	4			4	
3	175QJH20-52		52	5.5			4	
4	175QJH20-65		65	7.5			4	
5	175QJH20-78		78	7.5			6	
6	175QJH20-91		91	9.2			6	
7	175QJH20-104		104	11			6	
8	175QJH20-117		117	13			6	
9	175QJH20-130		130	13			6	
10	175QJH20-143		143	15			6	
11	175QJH20-156		156	15			6	
12	175QJH20-169		169	18.5			6	
13	175QJH20-182		182	18.5			6	
14	175QJH20-195		195	22			10	
15	175QJH20-208		208	22			10	
16	175QJH20-221		221	22			10	
17	175QJH20-234		234	25			16	
18	175QJH20-247		247	25			16	

175QJ32

编号 NO.	型号 Type	流量 Flow rate m ³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outler diamete r inch	配用电线 截面积 cable section mm ²	控制
1	175QJH32-24		24	4			4	可 根 据 用 户 需
2	175QJH32-36		36	5.5			4	
3	175QJH32-48		48	7.5			4	
4	175QJH32-60		60	9.2			6	
5	175QJH32-72		72	11			6	
6	175QJH32-84		84	13			6	
7	175QJH32-96		96	15			6	
8	175QJH32-108		108	18.5			6	
9	175QJH32-120		120	18.5			6	

编号 NO.	型号 Type	流量 Flow rate m ³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outler diamete r inch	配用电线 截面积 cable section mm ²	控制
1	175QJH50-24	50	24	5.5	163	3"	4	可根据用户需求匹配或厂家提出对应建议
2	175QJH50-36		36	9.2			4	
3	175QJH50-48		48	11			6	
4	175QJH50-60		60	13			6	
5	175QJH50-72		72	15			6	
6	175QJH50-84		84	18.5			6	
7	175QJH50-96		96	22			10	
8	175QJH50-108		108	25			10	
9	175QJH50-120		120	30			16	
10	175QJH50-132		132	30			16	
11	175QJH50-144		144	37			25	
12	175QJH50-156		156	37			25	
13	175QJH50-168		168	37			25	
14	175QJH50-180		180	45			25	
15	175QJH50-192		192	45			25	
16	175QJH50-204		204	45			25	
17	175QJH50-216		216	55			35	
18	175QJH50-228		228	55			35	
19	175QJH50-240		240	55			35	
20	175QJH50-252		252	63			35	
21	175QJH50-264		264	63			35	
22	175QJH50-276		276	75			50	
23	175QJH50-288		288	75			50	

当用户使用条件超出此范围时，请用户描述具体使用要求，我们可以按照用户得要求设计不同流量、扬程的潜水