

250QJ50									
高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter r mm	出水口径 Outler diameter r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJH50-20	50	20	5.5	233	3"	2.5	1241	120
2	250QJH50-40		40	9.2			6	1441	143
3	250QJH50-60		60	13			6	1651	173
4	250QJH50-80		80	18.5			10	1861	245
5	250QJH50-100		100	22			10	2055	266
6	250QJH50-120		120	30			16	2361	305
7	250QJH50-140		140	30			16	2496	321
8	250QJH50-160		160	37			25	2750	344
9	250QJH50-180		180	45			25	2985	383
10	250QJH50-200		200	45			25	3120	399
11	250QJH50-220		220	55			35	3013	426
12	250QJH50-240		240	55			35	3148	442
13	250QJH50-260		260	75		50	3395	487	
14	250QJH50-280		280	75		50	3530	503	
15	250QJH50-300		300	75		50	3805	551	
16	250QJH50-320		320	90		70	3940	567	
17	250QJH50-340		340	90		70	4075	583	
18	250QJH50-360		360	90		70	4302	627	
19	250QJH50-380		380	90		70	4437	643	
20	250QJH50-400		400	100		70	4572	659	
21	250QJH50-420		420	100		70	4707	675	
22	250QJH50-440		440	100		95	4935	710	
23	250QJH50-460		460	110		95	5070	726	
24	250QJH50-480		480	120		95	5205	742	
25	250QJH50-500		500	120		95	5410	831	
26	250QJH50-520		520	132		120	5640	875	
27	250QJH50-540		540	132		120	5775	891	
28	250QJH50-560		560	132		120	6010	937	
29	250QJH50-580		580	140	120	6145	953		
30	250QJH50-600		600	160	150	6280	969		
31	250QJH50-620		620	160	150	6415	1020		
32	250QJH50-640		640	160	150	6515	1040		
33	250QJH50-660		660	160	150	6715	1060		
34	250QJH50-680		680	185	185	6915	1160		
35	250QJH50-700		700	185	185	7015	1180		

250QJ80									
高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter r mm	出水口径 Outler diameter r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJH80-20		20	7.5			6	1260	128
2	250QJH80-40		40	15			10	1510	163
3	250QJH80-60		60	22			10	1663	237

4	250QJH80-80	80	80	30	234	4"	16	1868	276	
5	250QJH80-100		100	37			25	2068	299	
6	250QJH80-120		120	45			25	2258	338	
7	250QJH80-140		140	55			25	2473	365	
8	250QJH80-160		160	55			25	2608	381	
9	250QJH80-180		180	63			35	2855	426	
10	250QJH80-200		200	75			35	3130	474	
11	250QJH80-220		220	90			70	3357	518	
12	250QJH80-240		240	90			70	3492	534	
13	250QJH80-260		260	90			70	3627	550	
14	250QJH80-280		280	100			70	3855	585	
15	250QJH80-300		300	100			70	3990	601	
16	250QJH80-320		320	110			5"	95	4195	690
17	250QJH80-340		340	132				120	4425	734
18	250QJH80-360		360	132				120	4560	750
19	250QJH80-380		380	140				120	4895	816
20	250QJH80-400		400	140	120	5030		832		
21	250QJH80-420		420	140	120	5165		848		
22	250QJH80-440		440	150	120	5400		904		
23	250QJH80-460		460	160	120	5535		960		
24	250QJH80-480		480	185	150	5775		1016		
25	250QJH80-500		500	185	150	5910		1032		
26	250QJH80-530		530	185	150	4755		804		
27	250QJH80-560		560	185	150	5355		844		
28	250QJH80-590		590	200	280	150		5595	1087	
29	250QJH80-620		620	200		150		5750	1110	
30	250QJH80-650		650	220		150		5905	1182	
31	250QJH80-680		680	220		150		6060	1205	
32	250QJH80-710		710	220		150	6215	1228		

250QJ100高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJH100-20		20	9.2	234	4"	6	1328	130
2	250QJH100-40		40	18.5			10	1594	216
3	250QJH100-60		60	25			16	1827	248
4	250QJH100-80		80	37			25	2105	283
5	250QJH100-100		100	45			25	2338	322
6	250QJH100-120		120	55			25	2596	349
7	250QJH100-140		140	63		5"	35	2886	394
8	250QJH100-160		160	75			35	3204	442
9	250QJH100-180		180	75			35	3382	458
10	250QJH100-200		200	90			50	3652	502
11	250QJH100-220		220	100			70	3923	537
12	250QJH100-240		240	100			70	4101	553
13	250QJH100-260		260	110			70	4279	621
14	250QJH100-280		280	125			95	4622	686
15	250QJH100-300		300	125			95	4800	702
16	250QJH100-320		320	140			120	5178	768
17	250QJH100-340		340	150			120	5356	824

18	250QJH100-360	100	360	160			150	5634	880
19	250QJH100-380		380	160			150	5812	896
20	250QJH100-400		400	185			150	6095	952
21	250QJH100-420		420	185			150	6273	968
22	250QJH100-440		440	200			180	6746	1100
23	250QJH100-460		460	200	280		180	6924	1116
24	250QJH100-480		480	220			180	7102	1132
25	250QJH100-500		500	220			180	7350	1200
26	250QJH100-530		530	260			200	5920	1350
27	250QJH100-560		560	260			200	6075	1380
28	250QJH100-590	590	300	350	6"	220	6300	1410	
29	250QJH100-620	620	300			220	6455	1450	
30	250QJH100-650	650	300			220	6610	1510	
31	250QJH100-680	680	350			120*2	6770	1550	
32	250QJH100-710	710	350			120*2	6825	1623	
33	250QJH100-740	740	350			120*2	7078	1658	
34	250QJH100-770	770	410			150*2	7230	1710	
35	250QJH100-800	800	410			150*2	7385	1850	
36	250QJH100-830	830	410			150*2	7540	2087	

250QJ125					高度重量仅供参考				
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功 率 Power kw	外径 outside diamete r mm	出水口径 Outler diamete r inch	配用电 缆 截面积 cable section mm²	机组高 度 Height mm	机组重量 Weight kg
1	250QJH125-20	125	20	11	234	5"	6	1353	137
2	250QJH125-40		40	22			10	1614	221
3	250QJH125-60		60	37			25	1927	267
4	250QJH125-80		80	45			25	2160	306
5	250QJH125-100		100	55			25	2418	333
6	250QJH125-120		120	63			35	2708	378
7	250QJH125-140		140	75			35	3026	426
8	250QJH125-160		160	90			50	3296	470
9	250QJH125-180		180	100			50	3567	505
10	250QJH125-200		200	110			70	3815	594
11	250QJH125-220		220	125			70	4088	638
12	250QJH125-240		240	132			70	4366	684
13	250QJH125-260		260	150			95	4644	760
14	250QJH125-280		280	160			95	4922	816
15	250QJH125-300		300	160			95	5100	832
16	250QJH125-320		320	180			125	5383	888
17	250QJH125-340		340	180			125	5561	904
18	250QJH125-360		360	200	280		180	6034	1036
19	250QJH125-380		380	220			180	6282	1104
20	250QJH125-400		400	220			180	6160	1120
21	250QJH125-420		420	220	350		120*2	6638	1136
22	250QJH125-440		440	260			120*2	6156	1224
23	250QJH125-460		460	260			120*2	6334	1240
24	250QJH125-480		480	260			120*2	6512	1256
25	250QJH125-500		500	280			150*2	6795	1312
26	250QJH125-520		520	280			150*2	6973	1328
27	250QJH125-540		540	300			150*2	7151	1364

28	250QJH125-560		560	300			150*2	7329	1380
29	250QJH125-580		580	350			150*2	7652	1486
30	250QJH125-600		600	350			150*2	7380	1502

250QJ140	高度重量仅供参考
----------	----------

编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter r mm	出水口径 Outlet diameter r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg		
1	15	140	15	11	234	5"	6	1238	143		
2	30		30	18.5			10	1543	207		
3	45		45	30			16	1788	245		
4	60		60	45			25	2063	300		
5	75		75	55			35	2298	360		
6	90		90	63			35	2565	397		
7	105		105	75			35	2952	433		
8	120		120	90			50	3101	564		
9	135		135	90			50	3262	534		
10	150		150	100			50	3510	628		
11	165		165	110			70	3725	695		
12	180		180	125			70	3985	711		
13	195		195	140	280		70	4585	808		
14	210		210	140			95	4740	824		
15	225		225	160			120	4980	880		
16	240		240	160			120	5135	1013		
17	255		255	180			150	5400	1082		
18	270		270	180			150	5555	1098		
19	285		285	200			150	5950	1220		
20	300		300	200			180	5925	1250		
21	315		315	220			180	6150	1329		
22	330		330	220			180	6305	1359		
23	345		345	240			350	6"	180	5800	1562
24	360		360	240					180	5955	1622
25	375		375	260	120*2	6650			1652		
26	390		390	260	120*2	6265			1742		
27	405		405	280	120*2	6680			1802		
28	420		420	300	150*2	6835			1832		
29	435		435	300	150*2	6990			1952		
30	450		450	300	150*2	7290			2014		
31	465		465	350	150*2	7445			2054		
32	480		480	350	150*2	7600			2084		
33	495		495	350	150*2	7735			2162		
34	510		510	350	150*2	8060			2196		
35	525		525	410	150*2	8210			2222		
36	540		540	410	150*2	8365			2252		
37	555		555	410	150*2	8525			2282		
38	570		570	410	150*2	8830			2312		
39	585		585	450	150*2	8955			2350		
40	600		600	450	150*2	9025			2385		

250QJ160	高度重量仅供参考
----------	----------

编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diamete r mm	出水口径 Outler diamete r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	20	160	20	15	234	6"	10	1238	161
2	40		40	30			16	1543	233
3	60		60	45			25	1788	295
4	80		80	63			35	2063	380
5	100		100	75			35	2298	420
6	120		120	90			50	2656	537
7	140		140	100			50	2952	607
8	160		160	110			70	3101	780
9	180		180	132	280		70	3262	838
10	200		200	140			95	3510	908
11	220		220	160			120	3725	928
12	240		240	180			70*2	3985	999
13	260		260	180			70*2	4585	1071
14	280		280	200			95*2	4740	1165
15	300		300	220			95*2	4980	1186
16	320		320	220			95*2	5135	1207
17	340		340	240	350		120*2	5400	1288
18	360		360	260			120*2	5555	1309
19	380		380	260			120*2	5950	1420
20	400		400	350			120*2	5925	1441
21	420		420	350			150*2	6150	1462
22	440		440	350			150*2	6305	1573
23	460		460	350			150*2	5800	1600
24	480		480	350			150*2	5955	1615
25	500		500	350			150*2	6650	1636

250QJ200						高度重量仅供参考			
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diamete r mm	出水口径 Outler diamete r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	20	200	20	18. 5	234	6"	16	1318	272
2	40		40	45			25	1848	323
3	60		60	55			35	2113	376
4	80		80	75			50	2550	429
5	100		100	90			50	2827	565
6	120		120	110			70	3175	780
7	140		140	132	280		70	3455	807
8	160		160	150			95	3890	869
9	180		180	185			95	4010	925
10	200		200	185			95	4195	960
11	220		220	200			120	4895	1188
12	240		240	220			70*2	5035	1221
13	260		260	246			90*2	5125	1300

14	280		280	260	350		90*2	4860	1410
15	300		300	300			120*2	5150	1450
16	320		320	300			120*2	5335	1510
17	340		340	350			120*2	5665	1550
18	360		360	350			120*2	5850	1623
19	380		380	350			120*2	6035	1658
20	400		400	410			150*2	6370	1710
21	420		420	410			150*2	6555	1850
22	440		440	410			150*2	6740	2087

[illegible]

[illegible][illegible]

[illegible]