

150QJR10									
高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outlet diameter er	配用电线截 面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	150QJR10-28	10	28	3	138	2”	3	1280	59
2	150QJR10-37		37	4			3	1390	71
3	150QJR10-46		46	5.5			4	1505	82
4	150QJR10-56		55	7.5			4	1670	90
5	150QJR10-65		65	7.5			4	1760	95
6	150QJR10-74		74	9.2			6	1900	104
7	150QJR10-84		84	9.2			6	1990	109
8	150QJR10-93		93	11			6	2150	120
9	150QJR10-102		102	11			6	2240	125
10	150QJR10-112		112	13			10	2375	137
11	150QJR10-121		121	13			10	2465	142
12	150QJR10-130		130	15			10	2610	152
13	150QJR10-140		140	15			10	2700	162
14	150QJR10-149		149	18.5			16	2850	167
15	150QJR10-158		158	18.5			16	2940	172
16	150QJR10-167		167	18.5			16	3030	177
17	150QJR10-177		177	22			16	3190	205
18	150QJR10-186		186	22			16	3280	213
19	150QJR10-233		233	25			25	3830	253
20	150QJR10-279		279	30			25	4380	289
21	150QJR10-325	145	325	37	145		35	4930	326
22	150QJR10-372		372	45			35	5480	361

150QJR20									
高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outlet diameter er inch	配用电线截 面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	150QJR20-28	20	28	4	138	2”	3	1305	69
2	150QJR20-38		38	5.5			4	1425	75
3	150QJR20-47		47	7.5			4	1595	90
4	150QJR20-57		57	7.5			4	1690	96
5	150QJR20-67		67	9.2			6	1835	106
6	150QJR20-75		75	11			6	2000	118
7	150QJR20-85		85	11			6	2095	124
8	150QJR20-94		94	13			10	2235	137
9	150QJR20-103		103	15			10	2385	148
10	150QJR20-113		113	15			10	2480	154
11	150QJR20-122		122	18.5			16	2635	165
12	150QJR20-132		132	18.5			16	2730	171
13	150QJR20-141		141	18.5			16	2825	177
14	150QJR20-150		150	22			16	2990	209
15	150QJR20-160		160	22			16	3085	215

16	150QJR20-169		169	22			16	3180	221
17	150QJR20-179		179	25			16	3355	232
18	150QJR20-188		188	25			16	3450	238
19	150QJR20-235		235	30			25	4025	279
20	150QJR20-282		282	37	145		35	4600	321
21	150QJR20-239		329	45			35	5172	361

150QJR25 高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outlet diameter inch	配用电缆截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	150QJR25-24	25	24	3	138	2.5”	4		
2	150QJR25-32		32	4			4		
3	150QJR25-40		40	5.5			4		
4	150QJR25-48		48	5.5			4		
5	150QJR25-56		56	7.5			4		
6	150QJR25-64		64	7.5			4		
7	150QJR25-72		72	9.2			6		
8	150QJR25-80		80	9.2			6		
9	150QJR25-88		88	11			6		
10	150QJR25-96		96	11			6		
11	150QJR25-104		104	13			6		
12	150QJR25-112		112	13			6		
13	150QJR25-120		120	15			6		
14	150QJR25-128		128	15			6		
15	150QJR25-136		136	18.5			10		
16	150QJR25-144		144	18.5			10		
17	150QJR25-152		152	18.5			10		

150QJR32 高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outlet diameter inch	配用电缆截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	150QJR32-12	32	12	4	138	2.5”	4		
2	150QJR32-18		18	4			4		
3	150QJR32-24		24	4			4		
4	150QJR32-30		30	5.5			4		
5	150QJR32-36		36	5.5			4		
6	150QJR32-42		42	7.5			6		
7	150QJR32-48		48	9.2			6		
8	150QJR32-54		54	9.2			6		
9	150QJR32-60		60	11			6		
10	150QJR32-66		66	11			6		
11	150QJR32-72		72	13			6		
12	150QJR32-78		78	13			6		
13	150QJR32-84		84	13			6		

14	150QJR32-90		90	15			6		
15	150QJR32-96		96	15			6		
16	150QJR32-102		102	18.5			6		
17	150QJR32-108		108	18.5			10		
18	150QJR32-114		114	18.5			10		

150QJR40-50 高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diamet er mm	出水口 经 Outler diamet er inch	配用电线截 面积 cable section mm²	机组高 度 Height mm	机组重 量 Weight kg
1	150QJR40-8	40	8	3	138	2.5"	2.5		
2	150QJR40-16		16	4			2.5		
3	150QJR40-24		24	5.5			4		
4	150QJR40-32		32	7.5			4		
5	150QJR40-40		40	9.2			4		
6	150QJR40-48		48	9.2			6		
7	150QJR40-56		56	11			6		
8	150QJR40-64		64	13			6		
9	150QJR40-72		72	15			6		
10	150QJR40-80		80	18.5			6		
11	150QJR40-88		88	18.5			6		
12	150QJR40-96		96	18.5			6		
13	150QJR50-6	50	6	3			2.5		
14	150QJR50-12		12	4			4		
15	150QJR50-18		18	5.5			4		
16	150QJR50-24		24	7.5			4		
17	150QJR50-30		30	9.2			4		
18	150QJR50-36		36	9.2			6		
19	150QJR50-42		42	11			6		
20	150QJR50-48		48	13			6		
21	150QJR50-54		54	15			6		
22	150QJR50-60		60	18.5			6		
23	150QJR50-66		66	18.5			6		
24	150QJR50-72		72	18.5			6		

当用户使用条件超出此范围时，请用户描述具体使用要求，我们可以按照用户得要求设计不同流量、扬程的潜水电泵，