

250QJS50					高度重量仅供参考				
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJS50-20	50	20	5.5	233	3"	2.5	1241	120
2	250QJS50-40		40	9.2			6	1441	143
3	250QJS50-60		60	13			6	1651	173
4	250QJS50-80		80	18.5			10	1861	245
5	250QJS50-100		100	22			10	2055	266
6	250QJS50-120		120	30			16	2361	305
7	250QJS50-140		140	30			16	2496	321
8	250QJS50-160		160	37			25	2750	344
9	250QJS50-180		180	45			25	2985	383
10	250QJS50-200		200	45			25	3120	399
11	250QJS50-220		220	55			35	3013	426
12	250QJS50-240		240	55			35	3148	442
13	250QJS50-260		260	75		4"	50	3395	487
14	250QJS50-280		280	75			50	3530	503
15	250QJS50-300		300	75			50	3805	551
16	250QJS50-320		320	90			70	3940	567
17	250QJS50-340		340	90			70	4075	583
18	250QJS50-360		360	90			70	4302	627
19	250QJS50-380		380	90			70	4437	643
20	250QJS50-400		400	100			70	4572	659
21	250QJS50-420		420	100			70	4707	675
22	250QJS50-440		440	100			95	4935	710
23	250QJS50-460		460	110			95	5070	726
24	250QJS50-480		480	120			95	5205	742
25	250QJS50-500		500	120			95	5410	831
26	250QJS50-520		520	132			120	5640	875
27	250QJS50-540		540	132			120	5775	891
28	250QJS50-560		560	132			120	6010	937
29	250QJS50-580		580	140	235	120	6145	953	
30	250QJS50-600		600	160		150	6280	969	
31	250QJS50-620		620	160		150	6415	1020	
32	250QJS50-640		640	160		150	6515	1040	
33	250QJS50-660		660	160		150	6715	1060	
34	250QJS50-680		680	185		185	6915	1160	
35	250QJS50-700		700	185		185	7015	1180	

250QJS80					高度重量仅供参考				
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diameter inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJS80-20		20	7.5			6	1260	128

2	250QJS80-40	80	40	15	234	4"	10	1510	163	
3	250QJS80-60		60	22			10	1663	237	
4	250QJS80-80		80	30			16	1868	276	
5	250QJS80-100		100	37			25	2068	299	
6	250QJS80-120		120	45			25	2258	338	
7	250QJS80-140		140	55			25	2473	365	
8	250QJS80-160		160	55			25	2608	381	
9	250QJS80-180		180	63			35	2855	426	
10	250QJS80-200		200	75			35	3130	474	
11	250QJS80-220		220	90			70	3357	518	
12	250QJS80-240		240	90			70	3492	534	
13	250QJS80-260		260	90			70	3627	550	
14	250QJS80-280		280	100			70	3855	585	
15	250QJS80-300		300	100			5"	70	3990	601
16	250QJS80-320		320	110				95	4195	690
17	250QJS80-340		340	132				120	4425	734
18	250QJS80-360		360	132	120	4560		750		
19	250QJS80-380		380	140	120	4895		816		
20	250QJS80-400		400	140	120	5030		832		
21	250QJS80-420		420	140	120	5165		848		
22	250QJS80-440		440	150	120	5400		904		
23	250QJS80-460		460	160	120	5535		960		
24	250QJS80-480		480	185	150	5775		1016		
25	250QJS80-500		500	185	150	5910		1032		
26	250QJS80-530		530	185	150	4755		804		
27	250QJS80-560		560	185	150	5355		844		
28	250QJS80-590		590	200	280	150		5595	1087	
29	250QJS80-620		620	200		150		5750	1110	
30	250QJS80-650		650	220		150		5905	1182	
31	250QJS80-680		680	220		150	6060	1205		
32	250QJS80-710		710	220		150	6215	1228		

250QJS100高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outlet diameter inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJS100-20		20	9.2	234	4"	6	1328	130
2	250QJS100-40		40	18.5			10	1594	216
3	250QJS100-60		60	25			16	1827	248
4	250QJS100-80		80	37			25	2105	283
5	250QJS100-100		100	45			25	2338	322
6	250QJS100-120		120	55			25	2596	349
7	250QJS100-140		140	63			35	2886	394
8	250QJS100-160		160	75			35	3204	442
9	250QJS100-180		180	75			35	3382	458
10	250QJS100-200		200	90			50	3652	502
11	250QJS100-220		220	100			70	3923	537
12	250QJS100-240		240	100			70	4101	553
13	250QJS100-260		260	110			70	4279	621
14	250QJS100-280		280	125			95	4622	686

15	250QJS100-300	100	300	125	280	5"	95	4800	702
16	250QJS100-320		320	140			120	5178	768
17	250QJS100-340		340	150			120	5356	824
18	250QJS100-360		360	160			150	5634	880
19	250QJS100-380		380	160			150	5812	896
20	250QJS100-400		400	185			150	6095	952
21	250QJS100-420		420	185			150	6273	968
22	250QJS100-440		440	200			180	6746	1100
23	250QJS100-460		460	200			180	6924	1116
24	250QJS100-480		480	220			180	7102	1132
25	250QJS100-500		500	220			180	7350	1200
26	250QJS100-530		530	260			200	5920	1350
27	250QJS100-560		560	260			200	6075	1380
28	250QJS100-590		590	300	350	6"	220	6300	1410
29	250QJS100-620		620	300			220	6455	1450
30	250QJS100-650		650	300			220	6610	1510
31	250QJS100-680		680	350			120*2	6770	1550
32	250QJS100-710		710	350			120*2	6825	1623
33	250QJS100-740		740	350			120*2	7078	1658
34	250QJS100-770		770	410			150*2	7230	1710
35	250QJS100-800		800	410			150*2	7385	1850
36	250QJS100-830		830	410			150*2	7540	2087

250QJS125

高度重量仅供参考

编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outlet diameter inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	250QJS125-20	125	20	11	234	5"	6	1353	137
2	250QJS125-40		40	22			10	1614	221
3	250QJS125-60		60	37			25	1927	267
4	250QJS125-80		80	45			25	2160	306
5	250QJS125-100		100	55			25	2418	333
6	250QJS125-120		120	63			35	2708	378
7	250QJS125-140		140	75			35	3026	426
8	250QJS125-160		160	90			50	3296	470
9	250QJS125-180		180	100			50	3567	505
10	250QJS125-200		200	110			70	3815	594
11	250QJS125-220		220	125			70	4088	638
12	250QJS125-240		240	132			70	4366	684
13	250QJS125-260		260	150			95	4644	760
14	250QJS125-280		280	160			95	4922	816
15	250QJS125-300		300	160			95	5100	832
16	250QJS125-320		320	180			125	5383	888
17	250QJS125-340		340	180			125	5561	904
18	250QJS125-360		360	200	280		180	6034	1036
19	250QJS125-380		380	220			180	6282	1104
20	250QJS125-400		400	220			180	6160	1120
21	250QJS125-420		420	220			120*2	6638	1136
22	250QJS125-440		440	260			120*2	6156	1224
23	250QJS125-460		460	260			120*2	6334	1240

24	250QJS125-480		480	260	350		120*2	6512	1256
25	250QJS125-500		500	280			150*2	6795	1312
26	250QJS125-520		520	280			150*2	6973	1328
27	250QJS125-540		540	300			150*2	7151	1364
28	250QJS125-560		560	300			150*2	7329	1380
29	250QJS125-580		580	350			150*2	7652	1486
30	250QJS125-600		600	350			150*2	7380	1502

250QJS140					高度重量仅供参考					
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diamete r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg	
1	15	140	15	11	234	5"	6	1238	143	
2	30		30	18.5			10	1543	207	
3	45		45	30			16	1788	245	
4	60		60	45			25	2063	300	
5	75		75	55			35	2298	360	
6	90		90	63			35	2565	397	
7	105		105	75			35	2952	433	
8	120		120	90			50	3101	564	
9	135		135	90			50	3262	534	
10	150		150	100			50	3510	628	
11	165		165	110			70	3725	695	
12	180		180	125			70	3985	711	
13	195		195	140	280		70	4585	808	
14	210		210	140			95	4740	824	
15	225		225	160			120	4980	880	
16	240		240	160			120	5135	1013	
17	255		255	180			150	5400	1082	
18	270		270	180			150	5555	1098	
19	285		285	200			150	5950	1220	
20	300		300	200			180	5925	1250	
21	315		315	220			180	6150	1329	
22	330		330	220			180	6305	1359	
23	345		345	240		350	6"	180	5800	1562
24	360		360	240				180	5955	1622
25	375		375	260				120*2	6650	1652
26	390		390	260				120*2	6265	1742
27	405		405	280				120*2	6680	1802
28	420		420	300				150*2	6835	1832
29	435		435	300	150*2			6990	1952	
30	450		450	300	150*2			7290	2014	
31	465		465	350	150*2			7445	2054	
32	480		480	350	150*2			7600	2084	
33	495		495	350	150*2			7735	2162	
34	510		510	350	150*2			8060	2196	
35	525		525	410	150*2			8210	2222	
36	540		540	410	150*2			8365	2252	
37	555		555	410	150*2			8525	2282	
38	570		570	410	150*2			8830	2312	

39	585		585	450			150*2	8955	2350
40	600		600	450			150*2	9025	2385
250QJS160高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diamete r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	20	160	20	15	234	6"	10	1238	161
2	40		40	30			16	1543	233
3	60		60	45			25	1788	295
4	80		80	63			35	2063	380
5	100		100	75			35	2298	420
6	120		120	90			50	2656	537
7	140		140	100			50	2952	607
8	160		160	110			70	3101	780
9	180		180	132	280		70	3262	838
10	200		200	140			95	3510	908
11	220		220	160			120	3725	928
12	240		240	180			70*2	3985	999
13	260		260	180			70*2	4585	1071
14	280		280	200			95*2	4740	1165
15	300		300	220			95*2	4980	1186
16	320		320	220			95*2	5135	1207
17	340		340	240	350		120*2	5400	1288
18	360		360	260			120*2	5555	1309
19	380		380	260			120*2	5950	1420
20	400		400	350			120*2	5925	1441
21	420		420	350			150*2	6150	1462
22	440		440	350			150*2	6305	1573
23	460		460	350			150*2	5800	1600
24	480		480	350			150*2	5955	1615
25	500		500	350			150*2	6650	1636
250QJS200高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口径 Outler diamete r inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	20		20	18.5	234		16	1318	272
2	40		40	45			25	1848	323
3	60		60	55			35	2113	376
4	80		80	75			50	2550	429
5	100		100	90			50	2827	565
6	120		120	110			70	3175	780
7	140		140	132	280		70	3455	807
8	160		160	150			95	3890	869
9	180		180	185			95	4010	925

10	200	200	200	185	200	6"	95	4195	960
11	220		220	200	350		120	4895	1188
12	240		240	220			70*2	5035	1221
13	260		260	246			90*2	5125	1300
14	280		280	260			90*2	4860	1410
15	300		300	300			120*2	5150	1450
16	320		320	300			120*2	5335	1510
17	340		340	350			120*2	5665	1550
18	360		360	350			120*2	5850	1623
19	380		380	350			120*2	6035	1658
20	400		400	410			150*2	6370	1710
21	420		420	410			150*2	6555	1850
22	440		440	410		150*2	6740	2087	