

200QJW10										高度重量仅供参考									
编号 NO.		型号 Type		流量 Flow rate m³ /h		扬程 Head m		配用功率 Power kw		外径 outsi de diameter		出水口径 Outler diameter		配用电线 截面积 cable section mm²		机组高度 Height mm		机组重量 Weight kg	
1		200QJW10-47		10		47		4		184		2"		2.5		1337		79	
2		200QJW10-62				62		5.5						2.5		1472		90	
3		200QJW10-78				78		7.5						4		1582		101	
4		200QJW10-93				93		7.5						4		1722		110	
5		200QJW10-109				109		9.2						6		1851		129	
6		200QJW10-124				124		9.2						6		1977		134	
7		200QJW10-140				140		11						6		2122		146	
8		200QJW10-155				155		13						6		2256		157	
9		200QJW10-171				171		13						6		2417		171	
10		200QJW10-186				186		15						6		2527		181	
11		200QJW10-202				202		15						6		2761		201	
12		200QJW10-217				217		18.5						10		2871		209	
13		200QJW10-233				233		18.5						10		2981		238	
14		200QJW10-248				248		18.5						10		3157		246	
15		200QJW10-264				264		22						16		3267		254	
16		200QJW10-279				279		22						25		3482		274	
17		200QJW10-295				295		22						25		3592		282	
18		200QJW10-310				310		25						25		3702		306	
19		200QJW10-326				326		25						25		3812		314	
20		200QJW10-341				341		25						35		3922		322	
21		200QJW10-355				355		30						35		4032		355	

200QJW20										高度重量仅供参考									
编号 NO.		型号 Type		流量 Flow rate m³ /h		扬程 Head m		配用功率 Power kw		外径 outsi de diameter		出水口径 Outler diameter		配用电线 截面积 cable section mm²		机组高度 Height mm		机组重量 Weight kg	
1		200QJW20-13		20		13		3		184		2"		2.5		820		79	
2		200QJW20-26				26		3								940		90	
3		200QJW20-39				39		4								1377		101	
4		200QJW20-52				52		5.5								1472		110	
5		200QJW20-65				65		5.5								1582		129	
6		200QJW20-78				78		7.5						4		1722		134	
7		200QJW20-91				91		9.2						4		1851		146	
8		200QJW20-104				104		11						4		1977		157	
9		200QJW20-117				117		13						6		2122		171	
10		200QJW20-130				130		15						6		2256		181	
11		200QJW20-143				143		18.5						6		2417		201	
12		200QJW20-156				156		18.5						10		2527		209	
13		200QJW20-169				169		22				2.5"		10		2761		238	
14		200QJW20-182				182		22						10		2871		246	
15		200QJW20-195				195		22						10		2981		254	
16		200QJW20-208				208		25						10		3157		274	
17		200QJW20-221				221		25						10		3267		282	

18	200QJW20-234		234	30			10	3482	304
19	200QJW20-247		247	30			16	3592	314
20	200QJW20-260		260	30			16	3702	322
21	200QJW20-273		273	30		3"	16	3812	330
22	200QJW20-286		286	37			16	4013	355
23	200QJW20-299		299	37			16	4141	363
24	200QJW20-312		312	37			16	4251	371
25	200QJW20-325		325	37			16	4361	379
26	200QJW20-338		338	40			25	4581	406
27	200QJW20-351		351	40			25	4691	414
28	200QJW20-374		374	40			25	4801	422
29	200QJW20-378		378	45			25	4911	430
30	200QJW20-390		390	45			25	5021	435

200QJ32 高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³/h	扬程 Head m	配用功率 Power kw	外径 outside diameter	出水口 Outlet diameter	配用电线 截面 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJW32-13	32	13	4	184	3"	6	1197	95
2	200QJW32-26		26	5.5			6	1346	107
3	200QJW32-39		39	7.5			6	1454	116
4	200QJW32-52		52	9.2			6	1598	130
5	200QJW32-65		65	11			6	1901	145
6	200QJW32-78		78	13			6	1952	158
7	200QJW32-91		91	15			10	2045	173
8	200QJW32-104		104	18.5			10	2162	204
9	200QJW32-117		117	18.5			10	2281	211
10	200QJW32-130		130	22			10	2420	224
11	200QJW32-143		143	22			10	2539	231
12	200QJW32-156		156	25			16	2693	248
13	200QJW32-169		169	30			16	2847	268
14	200QJW32-182		182	30			16	2966	275
15	200QJW32-195		195	37			25	3150	289
16	200QJW32-208		208	37			25	3269	296
17	200QJW32-221		221	37			25	3388	303
18	200QJW32-234		234	45			35	3562	330
19	200QJW32-247		247	45			35	3861	337
20	200QJW32-260		260	45			35	3800	344
21	200QJW32-273		273	45			35	3919	351
22	200QJW32-286		286	55			35	4118	378
23	200QJW32-299		299	55			35	4237	385
24	200QJW32-312		312	55			50	4356	392
25	200QJW32-330		330	63		4"	50	3955	295
26	200QJW32-350		350	63			50	4080	310
27	200QJW32-370		370	75			70	4205	325
28	200QJW32-390		390	75			70	4430	340
29	200QJW32-410		410	75			70	4555	355
30	200QJW32-430		430	75			70	4680	370
31	200QJW32-450		450	75			70	4805	385
32	200QJW32-470		470	90			95	5080	400
33	200QJW32-490		490	90			95	5205	415

34	200QJW32-510	510	90	95	5330	430
35	200QJW32-530	530	90	95	5455	445
36	200QJW32-550	550	90	95	5580	460
37	200QJW32-570	570	100	95	5805	475
38	200QJW32-590	590	100	95	5930	590
39	200QJW32-610	610	110	95	6055	505
40	200QJW32-630	630	110	95	6280	520
41	200QJW32-650	650	110	95	6405	535

200QJW40

高度重量仅供参考

编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outsi de diameter	出水口 经 Outler diameter	配用电缆 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJW40-13	40	13	4	184	3"	6	1197	95
2	200QJW40-26		26	5.5			6	1346	107
3	200QJW40-39		39	7.5			6	1454	116
4	200QJW40-52		52	11			6	1623	138
5	200QJW40-65		65	13			6	1782	151
6	200QJW40-78		78	15			10	1926	166
7	200QJW40-91		91	18.5			10	2100	197
8	200QJW40-104		104	18.5			10	2219	204
9	200QJW40-117		117	22			10	2383	217
10	200QJW40-130		130	25			16	2547	234
11	200QJW40-143		143	25			16	2666	241
12	200QJW40-156		156	30			16	2885	261
13	200QJW40-169		169	37			25	3104	275
14	200QJW40-182		182	37			25	3223	282
15	200QJW40-195		195	37			25	3342	289
16	200QJW40-208		208	45			35	3566	316
17	200QJW40-221		221	45			35	3685	323
18	200QJW40-234		234	45			35	3804	330
19	200QJW40-247		247	45			35	3923	337
20	200QJW40-260		260	45			35	4042	344
21	200QJW40-273		273	55			35	3999	371
22	200QJW40-286		286	55			35	4118	378
23	200QJW40-299		299	63		4"	50	4349	429
24	200QJW40-312		312	63			50	4468	436
25	200QJW40-332		332	63			50	4587	443
26	200QJW40-352		352	63			50	4706	450
27	200QJW40-372		372	75			70	4825	457
28	200QJW40-392		392	75			70	5084	484
29	200QJW40-412		412	90			70	5203	491
30	200QJW40-432		432	90			70	5322	498
31	200QJW40-452		452	90			70	5441	505
32	200QJW40-472		472	90			70	5652	532
33	200QJW40-492		492	100			90	5771	539
34	200QJW40-512		512	100			90	5890	546

200QJW50

高度重量仅供参考

编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功 率 Power kw	外径 outsi de diamo ter	出水口 经 Outler diamo ter	配用电 缆 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJW50-13	50	13	4	184	3"	6	1228	98
2	200QJW50-26		26	7.5			6	1427	115
3	200QJW50-39		39	9.2			6	1572	132
4	200QJW50-52		52	13			6	1787	156
5	200QJW50-65		65	15			10	1962	174
6	200QJW50-78		78	18.5			10	2167	208
7	200QJW50-91		91	22			10	2362	224
8	200QJW50-104		104	25			16	2557	244
9	200QJW50-117		117	30			16	2807	267
10	200QJW50-130		130	30			16	2957	277
11	200QJW50-143		143	37			25	3207	294
12	200QJW50-156		156	37			25	3357	304
13	200QJW50-169		169	37			25	3507	314
14	200QJW50-182		182	45			25	3726	344
15	200QJW50-195		195	45			25	3912	354
16	200QJW50-208		208	45			35	4062	364
17	200QJW50-221		221	55			35	4050	394
18	200QJW50-234		234	55			35	4200	404
19	200QJW50-247		247	55			35	4350	414
20	200QJW50-260		260	55			35	4500	424
21	200QJW50-273		273	63		4"	50	4762	478
22	200QJW50-286		286	63			50	4912	488
23	200QJW50-299		299	75			70	5202	518
24	200QJW50-312		312	75			70	5352	528
25	200QJW50-332		332	75			70	5502	538
26	200QJW50-352		352	90			70	5652	548
27	200QJW50-372		372	90			70	5894	578
28	200QJW50-392		392	90			70	6044	588
29	200QJW50-412		412	90			70	6194	598
30	200QJW50-432		432	100			95	6494	608
31	200QJW50-452		452	100			95	6644	618
32	200QJW50-472		472	100			95	6887	628
33	200QJW50-492		492	110			120	7037	735
34	200QJW50-512		512	110			120	7178	755

200QJW63高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功 率 Power kw	外径 outsi de diamo ter mm	出水口 经 Outler diamo ter inch	配用电 缆 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJW63-15		15	5.5			2.5	885	98
2	200QJW63-30		30	9.2			4	1340	115
3	200QJW63-45		45	13			6	1530	132
4	200QJW63-60		60	18.5			10	1735	156
5	200QJW63-75		75	25			10	1905	174

6	200QJW63-90		90	30	184	4"	10	2117	208
7	200QJW63-105		105	37			16	2400	227
8	200QJW63-120		120	37			16	2525	244
9	200QJW63-135		135	45			25	2775	267
10	200QJW63-150		150	50			25	2880	277
11	200QJW63-165		165	50			25	3005	294
12	200QJW63-180		180	55			25	3197	304
13	200QJW63-195		195	63			35	3425	327
14	200QJW63-210		210	63			35	3577	344
15	200QJW63-225		225	75			50	3700	347
16	200QJW63-240		240	75			50	3895	364
17	200QJW63-255		255	75			50	4020	381
18	200QJW63-270		270	90			70	4195	397
19	200QJW63-285		285	90			70	4320	414
20	200QJW63-300		300	90			70	4495	431

200QJW80高度重量仅供参考									
编号 NO.	型号 Type	流量 Flow rate m³ /h	扬程 Head m	配用功率 Power kw	外径 outside diameter mm	出水口 经 Outlet diameter inch	配用电线 截面积 cable section mm²	机组高度 Height mm	机组重量 Weight kg
1	200QJW80-17	80	17	7.5	184	4"	4	1182	93
2	200QJW80-34		34	11			6	1382	98
3	200QJW80-51		51	18.5			10	1627	103
4	200QJW80-68		68	22			10	1886	113
5	200QJW80-85		85	30			16	2192	120
6	200QJW80-102		102	37			16	2436	128
7	200QJW80-119		119	40			25	2681	138
8	200QJW80-136		136	45			25	2816	145
9	200QJW80-153		153	55			25	2910	158
10	200QJW80-170		170	55			25	3045	166
11	200QJW80-187		187	63			35	3245	174
12	200QJW80-204		204	75			35	3575	197
13	200QJW80-221		221	75			35	3710	205
14	200QJW80-238		238	90			50	3955	207
15	200QJW80-255		255	90			50	4090	215
16	200QJW80-272		272	90			50	4225	223
17	200QJW80-289		289	100			50	4485	235
18	200QJW80-306		306	100			50	4620	243
19	200QJW80-323		323	110			75	4755	251
20	200QJW80-340		340	110			75	4890	259