

350XQB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	255	10.6	1450	34	37	80	1650	300	600-800
	0	290	8.85		30		81			
	0	220	6.85		28		79			
"-2°	0	270	10.5		37	40	79	1750		
	0	305	8.98		34		80			
	0	335	6.95		30		78			
0°	0	290	10.8		39	45	79	1950		
	0	330	9.08		37		80			
	0	365	7.08		33		78			
"+2°	0	210	11		43	45	79	1950		
	0	350	9.2		40		80			
	0	380	7.2		35		78			
"+4°	0	365	10		44	45	80	1950		
	0	375	9.4		44		80			
	0	405	7.4		39		78			

350XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	200	7.6	1450	20	22	77	1500	300	600-800
	0	230	5.8		16		80			
	0	250	3.9		13		78			
"-2°	0	215	7.7		21	30	78	1700		
	0	250	5.9		18		81			
	0	280	4.1		14		80			
0°	0	230	7.8		23	30	77	1700		
	0	270	6.0		20		81			
	0	300	4.3		16		80			
"+2°	0	250	7.9		26	30	77	1700		
	0	290	6.2		22		80			
	0	320	4.5		18		79			
"+4°	0	265	8.0		28	37	76	1700		
	0	305	6.3		24		80			
	0	335	4.6		20		81			

350XQB-85雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	230	7	1450	20	30	77	1700	300	600-800
	0	270	5.1		17		80			
	0	235	2.7		11		78			
"-2°	0	250	7.2		24	30	78	1700		
	0	290	5.5		19		81			
	0	330	4.2		13		80			
0°	0	270	7.5		27	37	77	1700		
	0	310	5.5		21		81			

	0	345	3.4		15		80		
"-2°	0	380	7.5		28	37	77	1700	
	0	530	5.7		23		80		
	0	370	3.4		17		79		
	0	300	7.6		31		76		
"-4°	0	355	5.9		26	37	80	1700	
	0	395	3.7		20		81		

350XQB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	245	5.8	1450	16	18.5	80	1500	300	600-800
	0	285	3.8		14		85			
	0	315	2.5		10		78			
"-2°	0	265	6.2		20	30	81	1700		
	0	305	4.2		15		85			
	0	335	2.7		11		80			
0°	0	280	6.5		22	30	81	1700		
	0	325	4.4		17		85			
	0	355	2.9		13		80			
"+2°	0	300	6.5		25	30	80	1700		
	0	355	4.7		19		85			
	0	380	3.2		15		80			
"+4°	0	320	6.7		28	37	79	1700		
	0	365	4.9		21		85			
	0	400	3.5		17		81			

350XQB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	205	5.8	1450	12	15	80	1250	300	600-800
	0	255	3.8		9		85			
	0	280	2.5		6		78			
"-2°	0	260	6.2		16	22	81	1550		
	0	305	4.2		12		85			
	0	330	2.7		9		80			
0°	0	300	6.5		21	22	81	1550		
	0	350	4.4		16		85			
	0	380	2.9		13		80			
"+2°	0	335	6.5		25	30	80	1700		
	0	390	4.7		20		85			
	0	420	3.2		16		80			
"+4°	0	400	6.7		33	37	79	1700		
	0	440	4.9		26		85			
	0	470	3.5		22		81			

350XQB-160雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-2°	0	290	6.2	1450	12	15	81	1250	300	600-800
	0	310	4.2		10		85			
	0	335	2.7		8		80			
0°	0	310	6.5		13	22	81	1550		
	0	350	4.4		12		85			

	0	370	2.9		10		80			
" +2°	0	365	6.5		18	22	80	1550		
	0	394	4.7		15		85			
	0	410	3.2		13		80			