

500XQB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	545	11.5	980	81	90	78	2100	450	800-900
	0	665	8.8		73		81			
	0	745	6		60		75			
"-2°	0	585	11.5		86	90	79	2100		
	0	710	9		78		82			
	0	790	6.2		66		76			
0°	0	625	11.6		93	110	79	2100		
	0	760	9.0		72		82			
	0	850	6.3		101		76			
"+2°	0	675	11.8		92	110	80	2100		
	0	805	9.2		79		82			
	0	900	6.5		109		75			
"+4°	0	735	12.0		100	110	80	2100		
	0	865	9.4		86		81			
	0	950	6.6		20		75			

500XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	380	9.5	980	50	55	78	1900	450	800-900
	0	490	7		42		81			
	0	570	4.4		31		75			
"-2°	0	480	8.2		51	55	79	1900		
	0	560	6.5		44		82			
	0	625	4.9		40		76			
0°	0	585	7.0		50	55	79	1900		
	0	600	6.3		45		82			
	0	695	3.9		34		76			
"+2°	0	650	6.6		52	55	80	1900		
	0	710	5.6		46		82			
	0	740	4.7		41		75			
"+4°	0	750	5.6		49	55	80	1900		
	0	760	4.8		47		81			
	0	794	4.4		43		75			

500XQB-85雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	540	7	980	50	55	78	1900	450	800-900
	0	605	5.4		42		81			
	0	685	3.1		30		75			
"-2°	0	585	7.1		55	75	79	2050		
	0	655	5.6		46		82			
	0	740	3.3		33		76			
0°	0	630	7.3		61	75	79	2050		
	0	700	5.8		51		82			
	0	780	3.5		36		76			
"+2°	0	655	7.4		64	75	80	2050		
	0	740	6.0		56		82			
	0	835	3.8		42		75			

″+4°	0	700	7.6		70	75	80	2050		
	0	788	6.3		62		81			
	0	885	4.1		48		75			
500XQB-100雪橇式轴流泵										
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
″-4°	0	575	5.7	980	40	55	78	1900	450	800-900
	0	650	4		31		81			
	0	720	2.4		22		75			
″-2°	0	620	5.8		45	55	79	1900		
	0	700	4.3		35		82			
	0	770	2.6		25		76			
0°	0	670	6.0		49	55	79	1900		
	0	750	4.5		40		82			
	0	820	3.0		29		76			
″+2°	0	710	6.2		55	75	80	2050		
	0	800	4.7		45		82			
	0	870	3.1		35		75			
″+4°	0	750	6.4		61	75	80	2050		
	0	840	4.9		50		81			
	0	920	3.4		40		75			
500XQB-125雪橇式轴流泵										
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
″-4°	0	515	3.8	980	27	37	78	1600	450	800-900
	0	580	2.6		21		81			
	0	870	1		17		75			
″-2°	0	620	4		35	55	79	1900		
	0	690	3		29		82			
	0	1015	1.5		25		76			
0°	0	720	4.5		45	55	79	1900		
	0	790	3.4		38		82			
	0	1150	1.9		36		76			
″+2°	0	800	4.9		55	75	80	2050		
	0	880	3.9		47		82			
	0	1260	2.5		46		75			
″+4°	0	900	5.2		72	75	80	2050		
	0	980	4.2		62		81			
	0	1400	2.9		64		75			
500XQB-160雪橇式轴流泵										
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
″-2°	0	660	3.2	980	27	37	81	1600	450	600-800
	0	740	2.2		21		85			
	0	760	1.9		19		80			
0°	0	740	3.5		35	45	81	1600		
	0	815	2.6		27		85			
	0	835	2.3		25		80			
″+2°	0	810	3.8		43	55	80	1900		
	0	895	2.9		34		85			
	0	910	2.7		31		80			