

600XQB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	780	9.1	730	89	110	78	2450	550	900-1000
	0	895	7.5		82		81			
	0	1020	4.9		67		75			
"-2°	0	830	9.2		96	110	79	2450		
	0	955	7.6		89		82			
	0	1090	5.0		76		76			
0°	0	885	9.3		103	110	79	2450		
	0	1080	7.7		96		82			
	0	1160	5.1		80		76			
"+2°	0	945	9.5		112	132	80	2700		
	0	1085	7.8		104		82			
	0	1225	5.3		88		75			
"+4°	0	1018	9.8		124	132	80	2700		
	0	1160	7.9		114		81			
	0	1300	5.4		95		75			

600XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	620	6.4	730	52	75	78	2450	550	900-1000
	0	730	5.6		47		81			
	0	770	3.7		35		75			
"-2°	0	670	6.5		55	75	79	2450		
	0	795	4.7		46		82			
	0	850	3.8		40		76			
0°	0	710	6.6		60	75	79	2450		
	0	850	4.8		50		82			
	0	915	3.9		43		76			
"+2°	0	780	6.7		66	75	80	2450		
	0	925	4.9		56		82			
	0	985	4.0		49		75			
"+4°	0	835	6.7		73	90	80	2450		
	0	975	4.98		60		81			
	0	1035	4.1		53		75			

600XQB-85雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	710	6	730	57	75	78	2450	550	900-1000
	0	830	4.4		45		81			
	0	940	2.3		31		75			
"-2°	0	770	6.2		64	75	79	2450		
	0	895	4.6		51		82			
	0	1015	2.5		35		76			
0°	0	825	6.3		71	75	79	2450		
	0	955	4.8		57		82			
	0	1075	2.7		35		76			
"+2°	0	865	6.4		75	90	80	2450		
	0	1015	4.9		62		82			
	0	1150	2.9		45		75			

"-4°	0	920	6.5		80	90	80	2450		
	0	1075	5.1		69		81			
	0	1215	3.2		52		75			

600XQB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³ /h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	690	4.8	730	42	55	78	2350	550	900-1000
	0	810	3.2		32		81			
	0	890	1.8		22		75			
"-2°	0	760	4.9		47	55	79	2350		
	0	885	3.4		36		82			
	0	975	2.0		25		76			
0°	0	820	5.1		52	55	79	2350		
	0	950	3.5		40		82			
	0	1045	2.2		29		76			
"+2°	0	880	5.3		58	75	80	2450		
	0	1015	3.8		45		82			
	0	1110	2.5		34		75			
"+4°	0	940	5.5		64	75	80	2450		
	0	1075	4.0		51		81			
	0	1180	2.7		39		75			

600XQB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	650	3.9	730	33	37	78	2000	550	900-1000
	0	790	2.5		24		81			
	0	880	1.3		15		75			
"-2°	0	800	4.2		43	45	79	2100		
	0	935	2.8		33		82			
	0	1035	1.7		23		76			
0°	0	930	4.5		55	55	79	2350		
	0	1075	3.2		44		82			
	0	1185	2.2		33		76			
"+2°	0	1025	4.8		67	75	80	2450		
	0	1180	3.6		53		82			
	0	1300	2.6		44		75			
"+4°	0	1150	5.2		88	90	80	2450		
	0	1320	4.1		71		81			
	0	1440	3.2		59		75			

600XQB-160雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-2°	0	895	2.7	730	32	37	81	2000	550	900-1000
	0	970	2.2		28		85			
	0	1030	1.6		21		80			
0°	0	995	3		40	45	81	2100		
	0	1095	2.2		31		85			
	0	1140	1.8		27		80			
"+2°	0	1075	3.2		48	55	80	2350		
	0	1220	2.5		39		85			
	0	1255	2.1		35		80			