

700QZB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1300	12.5	730	206	220	78	3120	6500	1100-1200
	0	1505	10.1		187		81			
	0	1670	7.1		163		75			
"-2°	0	1385	12.6		220	250	79	3200		
	0	1605	10.2		201		82			
	0	1785	7.2		171		76			
0°	0	1495	12.8		237	250	79	3200		
	0	1715	10.3		218		82			
	0	1905	7.4		186		76			
"+2°	0	1585	13.0		256	280	80	3340		
	0	1825	10.4		235		82			
	0	2015	7.6		204		75			
"+4°	0	1715	13.3		283	280	80	3340		
	0	1950	10.6		256		81			
	0	2125	7.7		221		75			

700QZB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1025	8.9	730	119	132	78	2600	6500	1100-1200
	0	1150	7.1		102		81			
	0	1305	4.7		78		75			
"-2°	0	1105	9.1		128	160	79	2900		
	0	1255	7.3		113		82			
	0	1435	4.9		87		76			
0°	0	1170	9.2		138	160	79	2900		
	0	1335	7.4		123		82			
	0	1535	5.0		95		76			
"+2°	0	1280	9.4		154	185	80	3050		
	0	1450	7.6		107		82			
	0	1665	5.2		170		75			
"+4°	0	1365	9.5		149	185	80	3050		
	0	1540	7.9		116		81			
	0	1745	5.3		221		75			

700QZB-85雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1255	7.5	730	121	132	78	2600	6500	1100-1200
	0	1365	6.1		105		81			
	0	1545	3.4		74		75			
"-2°	0	1365	7.7		135	160	79	2900		
	0	1480	6.5		118		82			
	0	1665	3.7		84		76			
0°	0	1460	7.9		148	160	79	2900		
	0	1580	6.6		131		82			
	0	1765	3.9		92		76			
"+2°	0	1535	8.0		158	185	80	3050		
	0	1675	6.8		143		82			
	0	1885	4.2		106		75			

"-4°	0	1640	8.3		169	185	80	3050		
	0	1785	7.1		158		81			
	0	1995	4.6		120		75			

700QZB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1015	4.5	590	51	55	78	2550	6500	1100-1200
	0	1170	3.2		39		81			
	0	1295	1.9		29		75			
"-2°	0	1095	4.7		57	75	79	2650		
	0	1255	3.3		44		82			
	0	1390	2.1		32		76			
0°	0	1180	4.8		63	75	79	2650		
	0	1345	3.5		50		82			
	0	1485	2.1		36		76			
"+2°	0	1255	4.9		70	75	80	2650		
	0	1430	3.7		56		82			
	0	1585	2.3		40		75			
"+4°	0	1329	5.1		78	90	80	2650		
	0	1505	3.8		62		81			
	0	1685	2.4		46		75			

700QZB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	830	4.9	730	56	75	78	2650	6500	1100-1200
	0	1080	2.7		38		81			
	0	1220	1.1		17		75			
"-2°	0	1080	5.3		75	90	79	2650		
	0	1335	3.0		52		82			
	0	1475	1.6		33		76			
0°	0	1330	5.7		98	110	79	2650		
	0	1580	3.5		70		82			
	0	1735	2.1		49		76			
"+2°	0	1550	6.1		119	132	80	2650		
	0	1825	4.1		94		82			
	0	1995	2.7		72		75			
"+4°	0	1720	6.5		150	185	80	3050		
	0	2015	4.6		116		81			
	0	2195	3.3		95		75			

700QZB-160雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	810	3.8	590	42	45	78	2350	6500	1100—1200
	0	1050	2.2		29		81			
	0	1155	1.4		21		75			
"-2°	0	1030	4		55	75	79	2650		
	0	1255	2.5		39		82			
	0	1370	1.6		29		76			
0°	0	1210	4.2		68	75	79	2650		
	0	1460	2.7		50		82			
	0	1590	1.9		39		76			

"+2°	0	1355	4. 4		81	90	80	2650		
	0	1630	3. 0		61		82			
	0	1770	2. 2		51		75			
"+4°	0	1550	4. 7		105	110	80	2750		
	0	1840	3. 4		78		81			
	0	1980	2. 6		68		75			