

900XQB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1850	10.0	490	239	250	78	3700	850	1400-1500
	0	2195	8.2		221		81			
	0	2545	5.0		174		75			
"-2°	0	1975	10.1		255	280	79	3850		
	0	2325	8.4		238		82			
	0	2715	5.2		191		76			
0°	0	2115	10.3		274	310	79	4050		
	0	2470	8.5		259		82			
	0	2890	5.4		209		76			
"+2°	0	2275	10.4		198	330	80			
	0	2630	8.7		280		82			
	0	3050	5.6		230		75			
"+4°	0	2485	10.7		329	350	80			
	0	2820	9.0		308		81			
	0	3215	5.8		252		75			

900XQB-50J雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1435	9.7	490	181	185	78	3400	850	1400-1500
	0	1795	7.8		170		81			
	0	2110	4.6		134		75			
"-2°	0	1570	9.8		200	220	79	3600		
	0	1980	7.9		183		82			
	0	2385	3.9		134		76			
0°	0	1555	10.3		212	250	79	3700		
	0	2155	8.1		202		82			
	0	2555	4.4		155		76			
"+2°	0	1825	10.3		233	250	80	3700		
	0	2220	8.3		215		82			
	0	2785	4.0		159		75			
"+4°	0	2075	9.9		248	250	80	3700		
	0	2467	8.4		239		81			
	0	2936	4.5		180		75			

900XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1480	7.0	490	135	160	78	3300	850	1400-1500
	0	1770	4.9		106		81			
	0	1940	3.5		86		75			
"-2°	0	1590	7.0		146	185	79	3400		
	0	1930	5.1		120		82			
	0	2135	3.6		96		76			
0°	0	1690	7.2		157	200	79	3600		
	0	2055	5.2		131		82			
	0	2290	3.8		105		76			
"+2°	0	1850	7.3		170	220	80	3700		
	0	2230	5.4		147		82			
	0	2480	3.9		119		75			

"-4°	0	1975	7.4		194	200	80	3000		
	0	2355	5.5		159		81			
	0	2595	3.9		129		75			

900XQB-70J雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1895	8.4	590	190	220	78	3550	850	1400-1500
	0	2155	6.5		163		81			
	0	2310	5.2		144		75			
"-2°	0	1955	8.7		204		79			
	0	2255	7.0		180		82			
	0	2440	5.4		158		76			
0°	0	2105	8.9		225	250	79	3600		
	0	2355	7.3		199		82			
	0	2570	5.7		176		76			
"+2°	0	2265	9.0		244	280	80	3750		
	0	2525	7.5		219		82			
	0	2715	6.4		207		75			
"+4°	0	2505	9.0		269	316	80	3900		
	0	2640	7.9		244		81			
	0	2780	7.1		236		75			

900XQB-70*雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	2275	7.7	490	223	250	78	3750	850	1400-1500
	0	2475	6.9		208		81			
	0	2765	5.0		177		75			
"-2°	0	2425	7.9		238		79			
	0	2655	7.0		222		82			
	0	2935	5.3		190		76			
0°	0	2565	8.5		253	280	79	3950		
	0	2800	7.1		236		82			
	0	3120	5.4		204		76			
"+2°	0	5775	8.6		277	315	80	4150		
	0	2985	7.1		254		82			
	0	3300	5.4		221		75			
"+4°	0	2735	8.7		297		80			
	0	3155	7.3		273		81			
	0	3490	5.6		239		75			

900XQB-85雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	1729	6.4	490	146	155	78	3290	850	1400-1500
	0	2015	4.7		119		81			
	0	2282	2.7		85		75			
"-2°	0	1896	6.5		164	180	79	3440		
	0	2196	4.8		132		82			
	0	2470	2.8		94		76			
0°	0	2044	6.5		180	200	79	3540		
	0	2355	4.9		144		82			
	0	2627	2.9		102		76			

"-2°	0	2157	6.6		188	200	80	3340		
	0	2512	5.0		157		82			
	0	2825	3.0		115		75			
"-4°	0	2319	6.7		202	220	80	3640		
	0	2691	5.1		172		81			
	0	3008	3.1		129		75			

900XQB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	1680	5.1	490	110	132	77	3290	850	1400-1500
	0	1968	3.5		84		80			
	0	2166	2.2		63		74			
"-4°	0	1868	5.2		122		78			
	0	2167	3.6		93		81			
	0	2368	2.3		69		75			
"-2°	0	2028	5.3		133	155	79			
	0	2335	3.7		102		82			
	0	2551	2.4		77		76			
0	0	2195	5.4		146		79			
	0	2510	3.8		112		82			
	0	2724	2.5		87		76			
"+2°	0	2353	5.5		160	180	80	3440		
	0	2688	3.9		124		82			
	0	2915	2.6		97		75			
"+4°	0	2515	5.6		174	200	80	3540		
	0	2864	4.0		134		81			
	0	3106	2.7		108		75			

900XQB-100T雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	2008	7.8	590	202	220	77	3540	850	1400-1500
	0	2334	5.6		160		80			
	0	2608	3.4		118		74			
"-4°	0	2236	7.9		224	250	78	3590		
	0	2575	5.7		177		81			
	0	2854	3.6		130		75			
"-2°	0	2433	8.0		245	280	79	3730		
	0	2779	5.8		194		82			
	0	3077	3.7		145		76			
0	0	2637	8.1		268	310	79	3840		
	0	2993	6.0		214		82			
	0	3291	3.9		160		76			
"+2°	0	2832	8.3		294		80			
	0	3210	6.1		235		82			
	0	3524	4.0		180		75			
"+4°	0	3027	8.4		318	330	80	3990		
	0	3421	6.2		252		81			
	0	3757	4.2		198		75			

900XQB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm

"-6°	0	1195	3.9	490	64	80	77	2906	850	1400-1500
	0	1510	2.5		48		80			
	0	1750	1.2		30		74			
"-4°	0	1593	4.0		84	90	78	2956		
	0	1910	2.7		64		81			
	0	2152	1.4		42		75			
"-2°	0	1994	4.2		108	132	79	3256		
	0	2301	2.9		84		82			
	0	2561	1.6		57		76			
0	0	2349	4.4		135	155	79			
	0	2693	3.1		106		82			
	0	2988	1.9		78		76			
"+2°	0	2645	4.6		160	180	80	3406		
	0	3019	3.4		128		82			
	0	3341	2.2		100		75			
"+4°	0	3038	4.9		204	220	80	3606		
	0	3430	3.7		162		81			
	0	3747	2.6		133		75			

900XQB-160雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-2°	0	2191	2.8	490	82	90	79	2956	850	1400-1500
	0	2356	2.3		69		82			
	0	2527	1.6		54		76			
0°	0	2487	3.0		99	110	79	3056		
	0	2656	2.5		84		82			
	0	2814	1.8		67		76			
"+2°	0	2778	3.2		120	132	80	3256		
	0	2965	2.7		101		82			
	0	3113	2.0		83		75			

