

1000XQB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³ /h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	2008	9.0	490	224	250	78	3755	870	1400-1500
	0	2060	8.9		222		81			
	0	2340	6.9		201		75			
"-2°	0	2140	10.3		273	315	79	4155		
	0	2415	9.2		260		82			
	0	2780	6.5		225		76			
0°	0	2367	10.8		319	355	79	4305		
	0	2687	9.7		300		82			
	0	3181	6.4		252		76			
"+2°	0	2753	10.9		372	400	80	4505		
	0	3091	9.6		343		82			
	0	3537	6.9		304		75			
"+4°	0	3050	10.7		406	450	80	4705		
	0	3396	9.4		384		81			
	0	3677	8.4		384		75			

1000XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³ /h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
″-4°	0	1871	8.0	490	180	200	82	3555	870	1400-1500
	0	2143	6.1		152		84			
	0	2209	5.6		145		84			
	0	2217	5.5		143		84			
	0	2456	3.8		111		82			
″-2°	0	2052	8.6		214	250	82	3755		
	0	2234	7.6		200		84			
	0	2464	6.1		173		85			
	0	2712	4.4		140		84			
	0	2811	3.6		121		82			
0°	0	2332	9.0		254	280	82	3955		
	0	2522	8.0		237		84			
	0	2835	6.0		197		86			
	0	3017	4.8		170		84			
	0	3124	3.9		148		82			
″+2°	0	2539	9.6		294	315	82	4155		
	0	2687	8.9		281		84			
	0	3041	6.9		241		86			
	0	3371	4.8		190		84			
	0	3503	4.0		170		82			
″+4°	0	2769	9.9	332		82				
	0	2967	9.1	316		84				
	0	3330	7.1	371		86				
	0	3626	5.3	224		84				

	0	3791	4.3		198	400	82	4555		
"-6°	0	3050	10.1		371		82			
	0	3297	8.8		341		84			
	0	3536	7.8		319		85			
	0	3874	6.0		270		84			
	0	3956	5.4		257		82			

1000XQB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	1891	5.1	490	115	132	82	3305	870	1400-1500
	0	2060	3.9		94		83			
	0	2220	3.1		84		82			
"-4°	0	2008	5.6		136	160	82			
	0	2308	3.9		106		84			
	0	2520	2.8		85		82			
"-2°	0	2149	5.9		152	185	82	3455		
	0	2514	4.0		118		84			
	0	2743	2.8		93		82			
0°	0	2303	6.0		167		82			
	0	2720	4.0		128		85			
	0	2940	2.9		102		82			
"+2°	0	2514	6.0		183	200	82	3555		
	0	2885	4.3		142		85			
	0	3114	3.1		116		82			
"+4°	0	2748	5.8		193	220	82	3655		
	0	3091	4.3		153		85			
	0	3279	3.4		134		82			

1000XQB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-4°	0	1979	5.0	490	121	132	78	3305	870	1400-1500	
	0	2557	2.8		82		81				
	0	2740	2.0		66		75				
"-2°	0	2208	5.0		134	160	79				
	0	2749	3.0		95		82				
	0	2977	2.1		76		76				
0°	0	2437	4.9		146		185				79
	0	2931	3.1		107						82
	0	3183	2.2		83						76
"+2°	0	2774	4.7		157	200	80	3455			
	0	3157	3.2		121		82				
	0	3400	2.4		98		75				
"+4°	0	3055	4.7		174	200	80	3555			
	0	3380	3.4		137		81				
	0	3580	2.7		119		75				

1200XQB-50雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³ /h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	2615	10.7	490	344	400	80	4318	950	1600—1800
	0	2683	10.7		343		82			
	0	3047	8.2		309		80			
"-2°	0	2786	12.2		420	450	80	4518		
	0	3144	11.0		401		85			
	0	3620	7.8		346		80			
0°	0	3081	12.9		490	560	80	4718		
	0	3498	11.6		463		86			
	0	4141	7.6		387		80			
"+2°	0	3585	12.9		571	630	80			
	0	4024	11.5		529		86			
	0	4606	8.2		467		80			
"+4°	0	3971	12.8		625	710	80	4768		
	0	4421	11.2		591		82			
	0	4787	10.0		590		80			

1200XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³ /h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	3195	9.3	490	351	400	83	4318	950	1600—1800
	0	3642	7.3		303		86			
	0	3902	5.8		266		83			
"-2°	0	3303	9.6		377	450	83	4518		
	0	3802	7.8		336		86			
	0	4133	6.0		292		83			
0°	0	3554	9.9		415	500	83	4718		
	0	3980	8.1		369		85			
	0	4337	6.3		326		83			
"+2°	0	3823	10.0		451	560	83	4718		
	0	4259	8.2		405		85			
	0	4582	7.1		383		83			
"+4°	0	4224	9.9		498	560	83	4718		
	0	4457	8.7		452		84			
	0	4695	7.8		437		83			

1200XQB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	2463	6.0		178	200	82	3556		
	0	2683	4.6		146		84			
	0	2891	3.7		129		82			
"-4°	0	2614	6.7		209	250	82	3756		
	0	3005	4.7		164		84			

	0	3281	3. 3	490	131		82		950	1600–1800
"-2°	0	2798	7. 0		234	280	82	3956		
	0	3273	4. 8		182		85			
	0	3572	3. 4		144		82			
0	0	2998	7. 2		257		82			
	0	3541	4. 8		197		85			
	0	3828	3. 4		156		82			
"+2°	0	3274	7. 2		282	315	82	4156		
	0	3756	5. 1		219		86			
	0	4054	3. 7		179		82			
"+4°	0	3578	6. 9		297	355	82	4306		
	0	4024	5. 1		236		85			
	0	4269	4. 0		206		82			

1200XQB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	2577	6.0	490	186	200	81	3556	950	1600—1800
	0	3329	3.3		127		85			
	0	3568	2.4		102		81			
"-2°	0	2874	5.9		206	220	81	3656		
	0	3579	3.5		146		85			
	0	3876	2.5		117		81			
0	0	3174	5.9		225	250	81	3756		
	0	3816	3.7		165		84			
	0	4144	2.6		128		81			
"+2°	0	3612	5.5		242	280	81	3956		
	0	4111	3.9		186		84			
	0	4426	2.8		151		81			
"+4°	0	3978	5.6		268	315	81	4156		
	0	4401	4.1		211		83			
	0	4661	3.3		184		81			

1200XQB-160雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-2°	0	2913	4.0	490	144	160	80	3408	950	1600-1800
	0	3327	2.9		111		84			
	0	3634	2.0		89		80			
0°	0	3441	3.9		163	185	80	3558		
	0	3863	2.9		131		83			
	0	4107	2.1		104		80			
"+2°	0	3997	3.7		180	200	80	3658		
	0	4314	3.1		160		82			
	0	4551	2.4		134		80			

1400XQB-70雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-4°	0	3392	9.5	365	393	450	80	4580	1250	1800-2000	
	0	4069	7.1		340		83				
	0	4634	4.9		268		82				
"-2°	0	3648	9.7		430	500	81	4780			
	0	4698	6.4		344		85				
	0	5183	4.6		287		81				
0°	0	3993	9.8		479	550	81				
	0	5015	6.6		379		85				
	0	5600	4.4		300		81				
"+2°	0	4321	9.8		514	590	81	4830			
	0	5426	6.2		413		85				
	0	6016	4.8		339		84				
"+4°	0	4800	9.5		556	640	81	4880			
	0	5727	7.0		459		85				
	0	6208	5.4		386		84				

1400XQB-100雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	4312	6.6	370	332	355	85	4180	1275	1800-2000
	0	4750	5.4		295		86			
	0	5300	3.7		229		85			
"-4°	0	4642	7.1		385	400	85	4380		
	0	5250	5.5		324		88			
	0	5870	3.5		297		85			
"-2°	0	5150	7.2		425	450	85	4580		
	0	5860	5.2		340		88			
	0	6350	3.6		262		86			
0	0	5450	7.4		466	500	85	4780		
	0	6210	5.5		381		88			
	0	6890	3.5		278		85			
"+2°	0	5900	7.3		496	560	85			
	0	6750	5.5		414		88			
	0	7380	3.8		324		85			
"+4°	0	6370	7.3		537	600	85	4880		
	0	7220	5.5		443		88			
	0	7830	4.0		362		85			

1400XQB-125雪橇式轴流泵

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	雪橇筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	3210	3.7		143	160	82	3180		
	0	3519	3.0		125		84			
	0	3733	2.4		110		81			
	0	3533	5.1		218		81			

"-4°	0	4398	3. 4	365	171	250	85	3630	1250	1800–2000
	0	4802	2. 3		132		82			
"-2°	0	4659	5. 2		289	330	82	4080		
	0	5373	3. 6		225		85			
	0	5872	2. 3		161		83			
0	0	5658	5. 1		336	400	84	4380		
	0	6443	3. 6		270		85			
	0	7013	2. 4		204		83			
"+2°	0	6300	5. 5		410	470	82	4680		
	0	7233	3. 6		303		85			
	0	7726	2. 9		268		82			
"+4°	0	7536	5. 2		468	540	82	4780		
	0	8226	4. 4		414		85			
	0	8511	3. 6		369		82			