

1600QZB-70型潜水轴流泵										QZB与QZ为相同型号	
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-4°	0	7273	8.2	295	693	800	84	5338	1480	2000-2200	
	0	8291	6.4		600		87				
	0	8882	5.1		525		84				
"-2°	0	7519	8.5		743		84				
	0	8655	6.8		665		87				
	0	9407	5.2		575		84				
0°	0	8089	8.7		819	900	84				5388
	0	9060	7.1		729		87				
	0	9872	5.6		642		84				
"+2°	0	8703	8.8		890	1000	84	5488			
	0	9695	7.2		801		86				
	0	10430	6.2		756		84				
"+4°	0	9614	8.7		982	1120	84				
	0	10145	7.7		896		86				
	0	10687	6.9		861		84				

1600QZB-100型潜水轴流泵										QZB与QZ为相同型号		
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸		
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm		
"-6°	0	5606	5.3	295	350	400	82	4588	1480	2000-2200		
	0	6107	4.1		287		83					
	0	6581	3.3		254		82					
"-4°	0	5951	5.9		412	450	82	4788				
	0	6840	4.1		324		84					
	0	7469	2.9		258		82					
"-2°	0	6370	6.2		462	500	82	4988				
	0	7450	4.2		360		84					
	0	8130	3.0		284		82					
0°	0	6825	6.3		506	560	82				5088	
	0	8061	4.2		389		85					
	0	8714	3.0		308		82					
"+2°	0	7452	6.3		555	630	82					
	0	8550	4.5		432		85					
	0	9229	3.2		353		82					
"+4°	0	8145	6.1		586		82					
	0	9160	4.5		467		85					
	0	9718	3.6		406		82					

1600QZB-125型潜水轴流泵										QZB与QZ为相同型号	
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-4°	0	5856	5.3	295	366	400	83	4588	1480	2000-2200	
	0	7577	2.9		251		86				
	0	8121	2.1		201		83				
"-2°	0	6543	5.2		405	450	83	4788			
	0	8147	3.1		289		86				
	0	8822	2.2		231		83				
0°	0	7224	5.2		443	500	83	4988			
	0	8686	3.3		326		83				
	0	9434	2.3		253		83				

"-2°	0	8222	4.9		476	560	83	4200		
	0	9358	3.4		367		85			
	0	10076	2.5		298		83			
"-4°	0	9055	4.9		528	630	83	5088		
	0	10018	3.6		417		84			
	0	10610	2.9		362		83			

1600QZB-160型潜水轴流泵											QZB与QZ为相同型
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-2°	0	6632	3.6	295	283	160	82	4238	1480	2000-2200	
	0	7573	2.5		219		85				
	0	8272	1.8		176		82				
0°	0	7833	3.4		320	185	82	4388			
	0	8794	2.5		258		84				
	0	9349	1.8		205		82				
"+2°	0	9098	3.3		355	200	82	4588			
	0	9820	2.7		315		83				
	0	10360	2.1		263		82				

1800QZB-70型潜水轴流泵										QZB与QZ为相同型号	
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-4°	0	7133	7.6	256.8	647	710	82	5238	1740	2400-2600	
	0	8044	5.8		544		84				
	0	8890	4.0		426		82				
"-2°	0	7673	7.7		699	800	83	5338			
	0	8769	6.0		608		84				
	0	9717	4.2		480		84				
0°	0	8131	7.8		751		83				5338
	0	9313	6.1		662		84				
	0	10376	4.4		534		84				
"+2°	0	8870	8.0		840	900	83				5338
	0	10083	6.3		743		84				
	0	11164	4.7		609		84				
"+4°	0	9035	8.1		921	1000	82	5488			
	0	10644	6.5		806		84				
	0	11665	4.8		665		83				

1800QZB-70*型潜水轴流泵											QZB与QZ为相同型号	
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸		
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm		
"-4°	0	9202	7.3	230	816	900	78	5338	1740	2400-2600		
	0	10162	6.4		752		84					
	0	11271	4.7		642		75					
"-2°	0	9765	7.5		869		82					
	0	10736	6.5		806		85					
	0	11923	4.9		695		79					
0	0	9983	7.8		941	1000	83	5488				
	0	11336	6.7		865		85					
	0	12604	5.1		755		82					
"+2°	0	10561	8.0		1002	1100	83	5588				
	0	11895	6.9		932		85					
	0	13246	5.3		822		82					

"-4°	0	11186	8.2		1075	1100	82	5500		
	0	12582	7.1		1008		85			
	0	13931	5.6		901		81			
"-6°	0	11798	8.3		1154	1200	79	5638		
	0	13204	7.3		1089		84			
	0	14610	5.8		988		79			

1800QZB-85型潜水轴流泵								QZB与QZ为相同型号				
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸		
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm		
"-4°	0	8237	7.0	256.8	696	800	81	5338	1740	2400-2600		
	0	9308	5.3		568		85					
	0	10184	3.5		447		78					
"-2°	0	8953	7.2		774	900	81				5338	
	0	10076	5.5		641		85					
	0	10981	3.8		500		81					
0	0	9579	7.3		855	900	81					5338
	0	10739	5.7		708		85					
	0	11645	4.0		560		81					
"+2°	0	10066	7.5		906	1000	84	5488				
	0	11389	5.9		778		85					
	0	12428	4.2		636		81					
"+4°	0	10722	7.7		981	1100	82	5588				
	0	12115	6.1		863		85					
	0	13183	4.5		719		81					

1800QZB-100型潜水轴流泵										QZB与QZ为相同型号	
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸	
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm	
"-6°	0	7969	5.6	256.8	512	560	85	4988	1740	2400-2600	
	0	9005	4.0		409		85				
	0	9787	2.6		317		80				
"-4°	0	8791	5.7		577	630	85	5088			
	0	9861	4.1		460		87				
	0	10653	2.8		357		83				
"-2°	0	9480	5.9		635	710	86	5238			
	0	10583	4.3		510		88				
	0	11428	3.0		407		84				
0	0	10201	6.0		701	800	86	5338			
	0	11325	4.5		570		88				
	0	12166	3.2		458		85				
"+2°	0	10883	6.2		772		86				
	0	12074	4.7		636		88				
	0	12960	3.5		522		85				
"+4°	0	11552	6.4	564	900	84					
	0	12794	4.9	704		88					
	0	13735	3.7	591		85					

1800QZB-125型潜水轴流泵										QZB与QZ为相同型号
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	6021	3.9		288	330	81	4388		
	0	6938	2.8		233		82			
	0	7681	1.8		180		75			

"-4°	0	7748	4.2	256.8	383	425	83	4688	1740	2400-2600
	0	8843	2.9		300		85			
	0	9420	2.1		248		82			
"-2°	0	9426	4.5		502	560	83	4988		
	0	10518	3.3		403		85			
	0	11329	2.3		312		82			
0	0	10949	4.9		635	710	83	5238		
	0	12160	3.7		528		85			
	0	13067	2.8		433		83			
"+2°	0	12179	5.2		764	900	82	5338		
	0	13483	4.1		648		85			
	0	14467	3.3		555		83			
"+4°	0	13791	5.7		998	1100	78	5588		
	0	15152	4.7		841		83			
	0	16133	3.9		740		83			

1800QZB-160型潜水轴流泵

QZB与QZ为相同型号

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-2°	0	10049	3.3	256.8	392	450	82	4788	1740	2400-2600
	0	11002	2.4		312		83			
	0	11471	1.9		266		81			
0°	0	11448	3.4		467	500	82	4988		
	0	12223	2.7		393		83			
	0	12666	2.3		339		82			
"+2°	0	12954	3.5		558	630	80	5088		
	0	13486	3.1		493		83			
	0	13916	2.6		435		82			

2000QZB-70型潜水轴流泵

QZB与QZ为相同型号

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
″-4°	0	9026	7.0	215	760	800	82	5338	2000	2400-2600
	0	10476	5.0		609		84			
	0	11315	3.7		497		82			
″-2°	0	9764	7.1		819	900	83			
	0	11501	5.1		676		85			
	0	12359	3.9		562		84			
0	0	10368	7.2		878	1000	83	5488		
	0	12291	5.1		734		85			
	0	13194	4.1		627		84			
″+2°	0	11352	7.3		979	1100	83	5588		
	0	13372	5.3		817		85			
	0	14187	4.3		716		84			
″+4°	0	12120	7.4		1068	1200	83	5638		
	0	14125	5.4		878		85			
	0	14814	4.5		782		84			

2000QZB-85型潜水轴流泵

QZB与QZ为相同型号

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-4°	0	10096	6.8		845	900	81	5338		
	0	11718	5.0		681		86			
	0	12988	3.2		520		79			

"-2°	0	10096	6.9	215	942	1000	81	5488	1740	2400-2600
	0	11718	5.2		761		86			
	0	12988	3.3		572		81			
0	0	11870	7.8		1037	1100	80	5588		
	0	13638	5.3		833		86			
	0	14943	3.5		627		82			
"+2°	0	12515	7.1		1090	1200	81	5638		
	0	14528	5.4		909		86			
	0	16024	3.7		711		81			
"+4°	0	13414	7.2		1169		82			
	0	15528	5.6		1001		86			
	0	17056	3.8		794		81			

2000QZB-100型潜水轴流泵 QZB与QZ为相同型号

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸		
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm		
"-6°	0	9639	5.6	215	645	710	83	5238	2000	2400-2600		
	0	11191	4.0		506		86					
	0	12339	2.6		384		81					
"-4°	0	10719	5.7		750	800	84	5338				
	0	12336	4.1		560		88					
	0	13506	2.7		426		83					
"-2°	0	11654	5.8		783	900	85				5338	
	0	13303	4.2		617		88					
	0	14550	2.8		475		84					
0	0	12623	5.9		856		85					5338
	0	14317	4.3		680		88					
	0	15560	2.9		527		84					
"+2°	0	13540	6.0		940	1000	85	5488				
	0	15345	4.4		748		88					
	0	16657	3.0		592		84					
"+4°	0	14462	6.1	1038	1100	83	5588					
	0	16345	4.5	819		88						
	0	17747	3.2	662		83						

2000QZB-125型潜水轴流泵 QZB与QZ为相同型号

安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
"-6°	0	6960	4.2	215	368	400	78	4588	2000	2400-2600
	0	8648	2.8		281		84			
	0	9774	1.7		210		75			
"-4°	0	9277	4.3		481	560	82	4988		
	0	10975	3.0		375		85			
	0	12110	1.8		277		79			
"-2°	0	11607	4.5		617	710	83	5238		
	0	13256	3.2		484		85			
	0	14469	2.1		359		82			
0	0	13705	4.7		763	800	83	5338		
	0	15553	3.4		612		85			
	0	16924	2.4		478		82			
"+2°	0	15448	4.9		902	1000	82	5488		
	0	17464	3.6		735		85			
	0	18970	2.6		603		81			
	0	17789	5.2	1147		79				

″+4°	0	19889	4.0		923	1200	84	5638		
	0	21373	3.0		794		79			
2000QZB-160型潜水轴流泵										
QZB与QZ为相同型号										
安装角度	流量Q		扬程	转速	功率N		效率	机组高度	叶轮直径	井筒尺寸
	m³/h	L/S	m	r/min	轴功率	电机功率	%	mm	mm	mm
″-2°	0	12551	3.2	215	479	560	81	4988	2000	2400-2600
	0	13895	2.3		373		83			
	0	14607	1.8		309		81			
0°	0	14262	3.3		572	630	81	5088		
	0	15615	2.5		452		83			
	0	16276	1.9		381		81			
″+2°	0	16150	3.4		679	710	80	5238		
	0	17415	2.7		548		83			
	0	18013	2.1		469		80			